

Applicant : HANGZHOU XIZI IPARKING CO., LTD.
NO.181 Hongda Road, Yuhang Economic Development Zone, Hangzhou, P.
R. China

Manufacturer : Same as above

Test Item : Chain driven lift-sliding mechanical parking system

Mark of origin : N/A

Type Designation(s) : PSHL-2-XI

Serial No(s). : Prototype

Test requirements : **Annex I of 2006/42/EC**

Essential health and safety requirements relating to the design and
construction of machine

Test result : The test item passed the test requirement(s).

Testing Laboratory : TÜV NORD (Hangzhou) Co., Ltd.
5 Floor, No.50 Jiuhuan Road, Jianggan District, Hangzhou, China.310019

Testing location : At manufacturer's premises

Compiled by (+ signature) : Ken Jia
TÜV NORD (Hangzhou) Co., Ltd.

Approved by (+ signature) : Jack Cai
TÜV NORD (Hangzhou) Co., Ltd.

Date of issue : 2019-05-28

Other Aspects:

This report is only valid together with other parts which named -01, -02 and -03.

The result of this report is established in the corrective measures provided by manufacturer include the design diagrams to the non-conformities for the test sample.

Test Report Format No. : TRF Annex I of 2006_42_EC_TNC

TRF Originator : TÜV NORD China, Date: 2011-10

Copyright © 2011 TÜV NORD China for Conformity Testing of Machinery, All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the TÜV NORD is acknowledged as copyright owner and source of the material. TÜV NORD takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test case verdicts:

Does not tested to the test object.....: N/T

Test case does not apply to the test object.....: N/A

Test item does meet the requirement.....: P(ass)

Test item does not meet the requirement.....: F(ail)

General remarks:

The test result presented in this report relate only to the object(s) tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

"(see Annex #)" refers to additional information appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a point is used as the decimal separator.

Additional Information :

Abbreviations used in this report :

None

Others:

The test sample was found not in compliance with the test requirements. The non-conformities were notified to the applicant. For clearance of those non-conformities, the technical documentation and proposed corrective measures to each non-conformities which submitted by applicant were considered acceptable for this test.

Brief description of the test item:

The product covered in this report was Lift-sliding mechanical parking system, the parking system extends the planar parking lot upwards. The model that certified this time is two layers on the ground type, with chain drive, and there may have 2-9 rows.

The system only can use the manual control mode that complied the standard, and the products were not complied the standard if auto mode were chosen.

Technical Specifications:

链条式升降横移类机械式停车设备 Chain driven lift-sliding mechanical parking system	
设备型号 Type	PSHL-2-XI
容车区域 Region	2
容车数量 Capacity	5
编 号 Product No.	201808218
日 期 Date	2018年12月5日
容车规格 Specification	CE
■ 车 长 Max. Length: ≤ 5300 mm	
■ 车 宽 Max. Width: ≤ 2000 mm	
■ 车 高 Max. Height: ≤ 1550 mm	
■ 车 重 Max. Weight: ≤ 2000 kg	
■ 电 源 Power Supply: 380V/50Hz	
■ 相 数 Number of Phase: 3 phases	
■ 满载电流 Full-load Current: 4 A	
■ 额定短时电流 Short-circuit Rating: 24A	
MADE IN CHINA	
XIZI 杭州西子智能停车股份有限公司 HANGZHOU XIZI IPARKING CO.,LTD.	
中国杭州余杭经济技术开发区宏达路181号 NO.181 Hongda Road, Yuhang Economic Development Zone, Hangzhou, P.R. China	

2006/42/EC Machinery Directive, Annex I Essential Health and Safety Requirements					
No.	Requirements	P	F	N/A	Remarks
1	Essential health and safety requirements				
1.1	General remarks				
1.1.2	Principles of safety integration				
	(a) Machinery must be designed and constructed so that it is fitted for its function, and can be operated, adjusted and maintained without putting persons at risk when these operations are carried out under the conditions foreseen but also taking into account any reasonably foreseeable misuse thereof.	X			EN ISO 12100 considered
	The aim of measures taken must be to eliminate any risk throughout the foreseeable lifetime of the machinery including the phases of transport, assembly, dismantling, disabling and scrapping.	X			EN ISO 12100 considered
	(b) Following principles applied				
	- elimination and reduction of risks as far as possible (inherently safe machinery design and construction),	X			
	- the necessary protection measures are taken in relation to risks that cannot be eliminated,	X			
	- information for users of the residual risks due to any shortcomings of the protection measures adopted, indication whether any particular training is required and specification of any need to provide personal protection equipment.	X			
	(c) When designing and constructing machinery and when drafting the instructions, the manufacturer or his authorised representative must envisage not only the intended use of the machinery but also any reasonably foreseeable misuse thereof.	X			
	The machinery must be designed and constructed in such a way as to prevent abnormal use if such use would engender a risk . Where appropriate, the instructions must draw the user's attention to ways — which experience has shown might occur — in which the machinery should not be used.	X			
	(d) Machinery must be designed and constructed to take account of the constraints to which the operator is subject as a result of the necessary or foreseeable use of personal protective equipment.	X			
	(e) Machinery must be supplied with all the special equipment and accessories essential to enable it to be adjusted, maintained and used safely.	X			
1.1.3	Materials and products				
	The materials used to construct machinery or products used or created during its use must not endanger persons' safety or health.	X			
	In particular, where fluids are used, machinery must be designed and constructed to prevent risks due to filling, use, recovery or draining.			X	

1.1.4	Lighting				
	Machinery must be supplied with integral lighting suitable for the operations concerned where the absence thereof is likely to cause a risk despite ambient lighting of normal intensity.			X	EN ISO 12100-2:2003, 4.8.6 No integral lighting
	Machinery must be designed and constructed so that there is no area of shadow likely to cause nuisance, that there is no irritating dazzle and that there are no dangerous stroboscopic effects on moving parts due to the lighting.			X	EN ISO 12100-2:2003, 5.2.1
	Internal parts requiring frequent inspection and adjustment, and maintenance areas must be provided with appropriate lighting.			X	EN ISO 12100-2:2003, 4.8.6 No integral lighting
1.1.5	Design of machinery to facilitate its handling				
	Machinery, or each component part thereof, must:				
	— be capable of being handled and transported safely,	X			EN ISO 121001, 4.6, 4.7, 4.14 & 6.5.1 a)
	— be packaged or designed so that it can be stored safely and without damage.	X			See above
	During the transportation of the machinery and/or its component parts, there must be no possibility of sudden movements or of hazards due to instability as long as the machinery and/or its component parts are handled in accordance with the instructions.	X			EN ISO 121001, 5.5.5, 6.1.2 & 6.5.1 a)
	Where the weight, size or shape of machinery or its various component parts prevents them from being moved by hand, the machinery or each component part must:				
	— either be fitted with attachments for lifting gear, or	X			EN ISO 12100, 5.5.5 & 6.5.1 a)
	— be designed so that it can be fitted with such attachments, or			X	
	— be shaped in such a way that standard lifting gear can easily be attached.			X	See above
	Where machinery or one of its component parts is to be moved by hand, it must:				
	— either be easily moveable, or			X	Not moved by hand
	— be equipped for picking up and moving safely.			X	See above
	Special arrangements must be made for the handling of tools and/or machinery parts which, even if lightweight, could be hazardous.			X	EN ISO 12100, 4.2.1
1.1.6	Ergonomics				
	Under the intended conditions of use, the discomfort, fatigue and physical and psychological stress faced by the operator must be reduced to the minimum possible, taking into account ergonomic principles such as:				
	— allowing for the variability of the operator's physical dimensions, strength and stamina,	X			
	— providing enough space for movements of the parts of the operator's body,	X			
	— avoiding a machine-determined work rate,	X			
	— avoiding monitoring that requires lengthy concentration,	X			

	— adapting the man/machinery interface to the foreseeable characteristics of the operators.	X			
1.1.7	Operating positions				
	The operating position must be designed and constructed in such a way as to avoid any risk due to exhaust gases and/or lack of oxygen.			X	No risk due to exhaust gases and/or lack of oxygen
	If the machinery is intended to be used in a hazardous environment presenting risks to the health and safety of the operator or if the machinery itself gives rise to a hazardous environment, adequate means must be provided to ensure that the operator has good working conditions and is protected against any foreseeable hazards.			X	No hazardous environment
	Where appropriate, the operating position must be fitted with an adequate cabin designed, constructed and/or equipped to fulfil the above requirements.			X	See above
	The exit must allow rapid evacuation. Moreover, when applicable, an emergency exit must be provided in a direction which is different from the usual exit.			X	See above
1.1.8	Seating				
	Where appropriate and where the working conditions so permit, work stations constituting an integral part of the machinery must be designed for the installation of seats.			X	No seats
	If the operator is intended to sit during operation and the operating position is an integral part of the machinery, the seat must be provided with the machinery.			X	See above
	The operator's seat must enable him to maintain a stable position. Furthermore, the seat and its distance from the control devices must be capable of being adapted to the operator.			X	See above
	If the machinery is subject to vibrations, the seat must be designed and constructed in such a way as to reduce the vibrations transmitted to the operator to the lowest level that is reasonably possible.			X	See above
	The seat mountings must withstand all stresses to which they can be subjected. Where there is no floor beneath the feet of the operator, footrests covered with a slip-resistant material must be provided.			X	See above
1.2	Control Systems				
1.2.1	Safety and reliability of control systems				
	Control systems must be designed and constructed in such a way as to prevent hazardous situations from arising. Above all, they must be designed and constructed in such a way that:				
	— they can withstand the intended operating stresses and external influences,	X			EN ISO 12100, 4.11.1; EN 60204-1, 9 to 12
	— a fault in the hardware or the software of the control system does not lead to hazardous situations,	X			EN ISO 12100-2:2003, 4.11.7
	— errors in the control system logic do not lead to hazardous situations,	X			
	— reasonably foreseeable human error during operation does not lead to hazardous situations.	X			EN ISO 12100, 4.8.1/4.8.7 & 5.2.7
	Particular attention must be given to the following points:				

	— the machinery must not start unexpectedly,	X			EN ISO 12100, 4.12; EN 60204-1, 9.2
	— the parameters of the machinery must not change in an uncontrolled way, where such change may lead to hazardous situations,	X			
	— the machinery must not be prevented from stopping if the stop command has already been given,	X			
	— no moving part of the machinery or piece held by the machinery must fall or be ejected,	X			
	— automatic or manual stopping of the moving parts, whatever they may be, must be unimpeded,	X			
	— the protective devices must remain fully effective or give a stop command,	X			
	— the safety-related parts of the control system must apply in a coherent way to the whole of an assembly of machinery and/or partly completed machinery.	X			
	For cable-less control, an automatic stop must be activated when correct control signals are not received, including loss of communication.			X	No cable-less control
1.2.2	Control devices				
	Control devices must be:				
	— clearly visible and identifiable, using pictograms where appropriate,	X			EN ISO 12100, 4.11.1; EN 60204-1, 9 to 12
	— positioned in such a way as to be safely operated without hesitation or loss of time and without ambiguity,	X			
	— designed in such a way that the movement of the control device is consistent with its effect,	X			
	— located outside the danger zones, except where necessary for certain control devices such as an emergency stop or a teach pendant,	X			The emergency stop located on-site
	— positioned in such a way that their operation cannot cause additional <u>risk</u> ,	X			No additional risk
	— designed or protected in such a way that the desired effect, where a hazard is involved, can only be achieved by a deliberate action,	X			Complied
	— made in such a way as to withstand foreseeable forces; particular attention must be paid to emergency stop devices liable to be subjected to considerable forces.	X			Complied
	Where a control device is designed and constructed to perform several different actions, namely where there is no one-to-one correspondence, the action to be performed must be clearly displayed and subject to confirmation, where necessary.			X	N/A
	Control devices must be so arranged that their layout, travel and resistance to operation are compatible with the action to be performed, taking account of ergonomic principles.	X			Complied
	Machinery must be fitted with indicators as required for safe operation. The operator must be able to read them from the control position.	X			Complied

	From each control position, the operator must be able to ensure that no-one is in the danger zones, or the control system must be designed and constructed in such a way that starting is prevented while someone is in the danger zone.			X	To be verified after installation
	If neither of these possibilities is applicable, before the machinery starts, an acoustic and/or visual warning signal must be given. The exposed persons must have time to leave the danger zone or prevent the machinery starting up.			X	
	If necessary, means must be provided to ensure that the machinery can be controlled only from control positions located in one or more predetermined zones or locations.			X	
	Where there is more than one control position, the control system must be designed in such a way that the use of one of them precludes the use of the others, except for stop controls and emergency stops.			X	N/A
	When machinery has two or more operating positions, each position must be provided with all the required control devices without the operators hindering or putting each other into a hazardous situation.			X	N/A
1.2.3	Starting				
	It must be possible to start machinery only by voluntary actuation of a control device provided for the purpose.	X			EN ISO 12100 EN 60204-1:2006, 7.5
	The same requirement applies:				
	— when restarting the machinery after a stoppage, whatever the cause,	X			
	— when effecting a significant change in the operating conditions.	X			
	However, the restarting of the machinery or a change in operating conditions may be effected by voluntary actuation of a device other than the control device provided for the purpose, on condition that this does not lead to a hazardous situation.	X			
	For machinery functioning in automatic mode, the starting of the machinery, restarting after a stoppage, or a change in operating conditions may be possible without intervention, provided this does not lead to a hazardous situation.	X			
	Where machinery has several starting control devices and the operators can therefore put each other in danger, additional devices must be fitted to rule out such risks .			X	
	If safety requires that starting and/or stopping must be performed in a specific sequence, there must be devices which ensure that these operations are performed in the correct order.	X			

1.2.4	Stopping				
1.2.4.1	Normal stop				
	Machinery must be fitted with a control device whereby the machinery can be brought safely to a complete stop.	X			EN ISO 12100, EN 60204-1, 9 to 12
	Each workstation must be fitted with a control device to stop some or all of the functions of the machinery, depending on the existing hazards, so that the machinery is rendered safe.	X			
	The machinery's stop control must have priority over the start controls.	X			
	Once the machinery or its hazardous functions have stopped, the energy supply to the actuators concerned must be cut off.	X			
1.2.4.2	Operational stop				
	Where, for operational reasons, a stop control that does not cut off the energy supply to the actuators is required, the stop condition must be monitored and maintained.	X			
1.2.4.3	Emergency stop				
	Machinery must be fitted with one or more emergency stop devices to enable actual or impending danger to be averted.	X			
	The following exceptions apply:				
	— machinery in which an emergency stop device would not lessen the <u>risk</u> , either because it would not reduce the stopping time or because it would not enable the special measures required to deal with the <u>risk</u> to be taken,			X	N/A
	— portable hand-held and/or hand-guided machinery.			X	N/A
	The device must:				
	— have clearly identifiable, clearly visible and quickly accessible control devices,	X			
	— stop the hazardous process as quickly as possible, without creating additional <u>risks</u> ,	X			
	— where necessary, trigger or permit the triggering of certain safeguard movements.			X	N/A
	Once active operation of the emergency stop device has ceased following a stop command,				
	— that command must be sustained by engagement of the emergency stop device until that engagement is specifically overridden;	X			
	— it must not be possible to engage the device without triggering a stop command;	X			
	— it must be possible to disengage the device only by an appropriate operation, and disengaging the device must not restart the machinery but only permit restarting.	X			
	The emergency stop function must be available and operational at all times, regardless of the operating mode.	X			
	Emergency stop devices must be a back-up to other safeguarding measures and not a substitute for them.	X			

1.2.4.4	Assembly of machinery				
	In the case of machinery or parts of machinery designed to work together, the machinery must be designed and constructed in such a way that the stop controls, including the emergency stop devices, can stop not only the machinery itself but also all related equipment, if its continued operation may be dangerous.			X	
1.2.5	Selection of control or operating modes				
	The control or operating mode selected must override all other control or operating modes, with the exception of the emergency stop.	X			EN 60204-1, 9
	If machinery has been designed and constructed to allow its use in several control or operating modes requiring different protective measures and/or work procedures, it must be fitted with a mode selector which can be locked in each position.	X			Key provided
	Each position of the selector must be clearly identifiable and must correspond to a single operating or control mode.	X			
	The selector may be replaced by another selection method which restricts the use of certain functions of the machinery to certain categories of operator.			X	N/A
	If, for certain operations, the machinery must be able to operate with a guard displaced or removed and/or a protective device disabled, the control or operating mode selector must simultaneously:				
	— disable all other control or operating modes,	X			
	— permit operation of hazardous functions only by control devices requiring sustained action,	X			
	— permit the operation of hazardous functions only in reduced risk conditions while preventing hazards from linked sequences,	X			
	— prevent any operation of hazardous functions by voluntary or involuntary action on the machine's sensors.	X			
	If these four conditions cannot be fulfilled simultaneously, the control or operating mode selector must activate other protective measures designed and constructed to ensure a safe intervention zone.			X	N/A
	In addition, the operator must be able to control operation of the parts he is working on from the adjustment point.			X	
1.2.6	Failure of the power supply				
	The interruption, the re-establishment after an interruption or the fluctuation in whatever manner of the power supply to the machinery must not lead to dangerous situations.	X			
	Particular attention must be given to the following points:				
	— the machinery must not start unexpectedly,	X			Reset control provided
	— the parameters of the machinery must not change in an uncontrolled way when such change can lead to hazardous situations,	X			
	— the machinery must not be prevented from stopping if the command has already been given,	X			

	— no moving part of the machinery or piece held by the machinery must fall or be ejected,	X			
	— automatic or manual stopping of the moving parts, whatever they may be, must be unimpeded,	X			
	— the protective devices must remain fully effective or give a stop command.	X			
1.3	Protection against mechanical hazards				
1.3.1	Loss of stability				
	Machinery and its components and fittings must be stable enough to avoid overturning, falling or uncontrolled movements during transportation, assembly, dismantling and any other action involving the machinery.	X			
	If the shape of the machinery itself or its intended installation does not offer sufficient stability, appropriate means of anchorage must be incorporated and indicated in the instructions.			X	See above
1.3.2	<u>Risk</u> of break-up during operation				
	The various parts of machinery and their linkages must be able to withstand the stresses to which they are subject when used.	X			EN ISO 12100, 5.2.7
	The durability of the materials used must be adequate for the nature of the working environment foreseen by the manufacturer or his authorised representative, in particular as regards the phenomena of fatigue, ageing, corrosion and abrasion.	X			
	The instructions must indicate the type and frequency of inspections and maintenance required for safety reasons. They must, where appropriate, indicate the parts subject to wear and the criteria for replacement.	X			EN ISO 12100, 6
	Where a <u>risk</u> of rupture or disintegration remains despite the measures taken, the parts concerned must be mounted, positioned and/or guarded in such a way that any fragments will be contained, preventing hazardous situations.	X			EN ISO 12100, 5.2.7
	Both rigid and flexible pipes carrying fluids, particularly those under high pressure, must be able to withstand the foreseen internal and external stresses and must be firmly attached and/or protected to ensure that no <u>risk</u> is posed by a rupture.			X	No flexible pipes carrying fluids
	Where the material to be processed is fed to the tool automatically, the following conditions must be fulfilled to avoid <u>risks</u> to persons:				
	— when the workpiece comes into contact with the tool, the latter must have attained its normal working condition,	X			
	— when the tool starts and/or stops (intentionally or accidentally), the feed movement and the tool movement must be coordinated.	X			
1.3.3	<u>Risks</u> due to falling or ejected objects				
	Precautions must be taken to prevent <u>risks</u> from falling or ejected objects.	X			

1.3.4	<u>Risks</u> due to surfaces, edges or angles				
	Insofar as their purpose allows, accessible parts of the machinery must have no sharp edges, no sharp angles and no rough surfaces likely to cause injury.	X			
1.3.5	<u>Risks</u> related to combined machinery				
	Where the machinery is intended to carry out several different operations with manual removal of the piece between each operation (combined machinery), it must be designed and constructed in such a way as to enable each element to be used separately without the other elements constituting a <u>risk</u> for exposed persons.	X			
	For this purpose, it must be possible to start and stop separately any elements that are not protected.	X			
1.3.6	<u>Risks</u> related to variations in operating conditions				
	Where the machinery performs operations under different conditions of use, it must be designed and constructed in such a way that selection and adjustment of these conditions can be carried out safely and reliably.	X			
1.3.7	<u>Risks</u> related to moving parts				
	The moving parts of machinery must be designed and constructed in such a way as to prevent <u>risks</u> of contact which could lead to accidents or must, where <u>risks</u> persist, be fitted with guards or protective devices.	X			
	All necessary steps must be taken to prevent accidental blockage of moving parts involved in the work. In cases where, despite the precautions taken, a blockage is likely to occur, the necessary specific protective devices and tools must, when appropriate, be provided to enable the equipment to be safely unblocked.	X			
	The instructions and, where possible, a sign on the machinery shall identify these specific protective devices and how they are to be used.	X			
1.3.8	Choice of protection against <u>risks</u> arising from moving parts				
	Guards or protective devices designed to protect against <u>risks</u> arising from moving parts must be selected on the basis of the type of <u>risk</u> . The following guidelines must be used to help to make the choice.	X			
1.3.8.1	Moving transmission parts				
	Guards designed to protect persons against the hazards generated by moving transmission parts must be:				
	— either fixed guards as referred to in section 1.4.2.1, or	X			
	— interlocking movable guards as referred to in section 1.4.2.2.			X	
	Interlocking movable guards should be used where frequent access is envisaged.			X	
1.3.8.2	Moving parts involved in the process				
	Guards or protective devices designed to protect persons against the hazards generated by moving parts involved in the process must be:				
	— either fixed guards as referred to in section 1.4.2.1, or	X			Fixed guard provided

	— interlocking movable guards as referred to in section 1.4.2.2, or			X	
	— protective devices as referred to in section 1.4.3, or			X	
	— a combination of the above.			X	
	However, when certain moving parts directly involved in the process cannot be made completely inaccessible during operation owing to operations requiring operator intervention, such parts must be fitted with:				
	— fixed guards or interlocking movable guards preventing access to those sections of the parts that are not used in the work, and			X	
	— adjustable guards as referred to in section 1.4.2.3 restricting access to those sections of the moving parts where access is necessary.			X	
1.3.9	Risks of uncontrolled movements				
	When a part of the machinery has been stopped, any drift away from the stopping position, for whatever reason other than action on the control devices, must be prevented or must be such that it does not present a hazard.	X			EN 60204-1, 9.2.5.1, 9.2.5.5
1.4	Required characteristics of guard and protection devices				
1.4.1	General requirement				
	Guards and protective devices must:				
	— be of robust construction,	X			EN ISO 12100
	— be securely held in place,	X			See above
	— not give rise to any additional hazard,	X			See above
	— not be easy to by-pass or render non-operational,	X			See above
	— be located at an adequate distance from the danger zone,	X			See above
	— cause minimum obstruction to the view of the production process, and	X			See above
	— enable essential work to be carried out on the installation and/or replacement of tools and for maintenance purposes by restricting access exclusively to the area where the work has to be done, if possible without the guard having to be removed or the protective device having to be disabled.	X			See above
	In addition, guards must, where possible, protect against the ejection or falling of materials or objects and against emissions generated by the machinery.	X			See above
1.4.2	Special requirements for guards				
1.4.2.1	Fixed guards				
	Fixed guards must be fixed by systems that can be opened or removed only with tools.	X			EN ISO 12100, 5.3.2.2
	Their fixing systems must remain attached to the guards or to the machinery when the guards are removed.	X			See above
	Where possible, guards must be incapable of remaining in place without their fixings.	X			See above

1.4.2.2	Interlocking moveable guards	No this interlocking moveable guard			
	Interlocking movable guards must:				
	— as far as possible remain attached to the machinery when open,			X	
	— be designed and constructed in such a way that they can be adjusted only by means of an intentional action.			X	
	Interlocking movable guards must be associated with an interlocking device that:				
	— prevents the start of hazardous machinery functions until they are closed and			X	
	— gives a stop command whenever they are no longer closed.			X	
	Where it is possible for an operator to reach the danger zone before the risk due to the hazardous machinery functions has ceased, movable guards must be associated with a guard locking device in addition to an interlocking device that:				
	— prevents the start of hazardous machinery functions until the guard is closed and locked, and			X	
	— keeps the guard closed and locked until the risk of injury from the hazardous machinery functions has ceased.			X	
	Interlocking movable guards must be designed in such a way that the absence or failure of one of their components prevents starting or stops the hazardous machinery functions.			X	
1.4.2.3	Adjustable guards restricting access				
	Adjustable guards restricting access to those areas of the moving parts strictly necessary for the work must be:				
	— adjustable manually or automatically, depending on the type of work involved, and			X	
	— readily adjustable without the use of tools.			X	
1.4.3	Special requirements for protection devices				
	Protective devices must be designed and incorporated into the control system in such a way that:				
	— moving parts cannot start up while they are within the operator's reach,			X	
	— persons cannot reach moving parts while the parts are moving, and			X	
	— the absence or failure of one of their components prevents starting or stops the moving parts.			X	
	Protective devices must be adjustable only by means of an intentional action.			X	
1.5	Risks due to other hazards				
1.5.1	Electricity supply				
	Where machinery has an electricity supply, it must be designed, constructed and equipped in such a way that all hazards of an electrical nature are or can be prevented.	X			EN 60204-1, 6

	The safety objectives set out in Directive 2006/95/EC shall apply to machinery. However, the obligations concerning conformity assessment and the placing on the market and/or putting into service of machinery with regard to electrical hazards are governed solely by this Directive.	X			See above
1.5.2	Static electricity				
	Machinery must be designed and constructed to prevent or limit the build-up of potentially dangerous electrostatic charges and/or be fitted with a discharging system.	X			EN ISO 12100
1.5.3	Energy supply other than electricity				
	Where machinery is powered by source of energy other than electricity, it must be so designed, constructed and equipped as to avoid all potential risks associated with such sources of energy.	X			EN 983:1996; EN ISO 12100
1.5.4	Errors of fitting				
	Errors likely to be made when fitting or refitting certain parts which could be a source of risk must be made impossible by the design and construction of such parts or, failing this, by information given on the parts themselves and/or their housings.	X			EN ISO 12100
	The same information must be given on moving parts and/or their housings where the direction of movement needs to be known in order to avoid a risk .	X			See above
	Where necessary, the instructions must give further information on these risks .	X			See above
	Where a faulty connection can be the source of risk , incorrect connections must be made impossible by design or, failing this, by information given on the elements to be connected and, where appropriate, on the means of connection.	X			See above
1.5.5	Extreme temperatures				
	Steps must be taken to eliminate any risk of injury arising from contact with or proximity to machinery parts or materials at high or very low temperatures.			X	
	The necessary steps must also be taken to avoid or protect against the risk of hot or very cold material being ejected.			X	
1.5.6	Fire				
	Machinery must be designed and constructed in such a way as to avoid any risk of fire or overheating posed by the machinery itself or by gases, liquids, dust, vapours or other substances produced or used by the machinery.	X			EN ISO 12100
1.5.7	Explosion				
	Machinery must be designed and constructed in such a way as to avoid any risk of explosion posed by the machinery itself or by gases, liquids, dust, vapours or other substances produced or used by the machinery.			X	No explosion likely
	Machinery must comply, as far as the risk of explosion due to its use in a potentially explosive atmosphere is concerned, with the provisions of the specific Community Directives.			X	94/9/EC - ATEX

1.5.8	Noise				
	Machinery is so designed and constructed that risks resulting from the emission of airborne noise are reduced to the lowest level taking account of technical progress and the availability of means of reducing noise, in particular at source.	X			<75 dB(A) (see 1.1.1 e)
1.5.9	Vibrations				
	Machinery must be designed and constructed in such a way that risks resulting from vibrations produced by the machinery are reduced to the lowest level, taking account of technical progress and the availability of means of reducing vibration, in particular at source.	X			
	The level of vibration emission may be assessed with reference to comparative emission data for similar machinery.	X			See above
1.5.10	Radiation				
	Undesirable radiation emissions from the machinery must be eliminated or be reduced to levels that do not have adverse effects on persons.			X	
	Any functional ionising radiation emissions must be limited to the lowest level which is sufficient for the proper functioning of the machinery during setting, operation and cleaning. Where a risk exists, the necessary protective measures must be taken.			X	See above
	Any functional non-ionising radiation emissions during setting, operation and cleaning must be limited to levels that do not have adverse effects on persons.			X	See above
1.5.11	External radiation				
	Machinery must be designed and constructed in such a way that external radiation does not interfere with its operation.			X	See 1.5.10
1.5.12	Laser radiation				
	Where laser equipment is used, the following should be taken into account:			X	See 1.5.10
	— laser equipment on machinery must be designed and constructed in such a way as to prevent any accidental radiation,			X	See above
	— laser equipment on machinery must be protected in such a way that effective radiation, radiation produced by reflection or diffusion and secondary radiation do not damage health,			X	See above
	— optical equipment for the observation or adjustment of laser equipment on machinery must be such that no health risk is created by laser radiation.			X	See above
1.5.13	Emission of hazardous materials and substances				
	Machinery must be designed and constructed in such a way that risks of inhalation, ingestion, contact with the skin, eyes and mucous membranes and penetration through the skin of hazardous materials and substances which it produces can be avoided.	X			

	Where a hazard cannot be eliminated, the machinery must be so equipped that hazardous materials and substances can be contained, evacuated, precipitated by water spraying, filtered or treated by another equally effective method.	X			See above
	Where the process is not totally enclosed during normal operation of the machinery, the devices for containment and/or evacuation must be situated in such a way as to have the maximum effect.	X			See above
1.5.14	<u>Risk</u> of being trapped in a machine				
	Machinery must be designed, constructed or fitted with a means of preventing a person from being enclosed within it or, if that is impossible, with a means of summoning help.	X			
1.5.15	<u>Risk</u> of slipping, tripping or falling				
	Parts of the machinery where persons are liable to move about or stand must be designed and constructed in such a way as to prevent persons slipping, tripping or falling on or off these parts.			X	
	Where appropriate, these parts must be fitted with handholds that are fixed relative to the user and that enable them to maintain their stability.			X	See above
1.5.16	Lightning				
	Machinery in need of protection against the effects of lightning while being used must be fitted with a system for conducting the resultant electrical charge to earth.			X	See above
1.6	Maintenance				
1.6.1	Machinery maintenance				
	Adjustment and maintenance points must be located outside danger zones. It must be possible to carry out adjustment, maintenance, repair, cleaning and servicing operations while machinery is at a standstill.	X			
	If one or more of the above conditions cannot be satisfied for technical reasons, measures must be taken to ensure that these operations can be carried out safely (see section 1.2.5).	X			when perform the maintenance, hazardous moving are stopped by the interlocking protection control system provided
	In the case of automated machinery and, where necessary, other machinery, a connecting device for mounting diagnostic fault-finding equipment must be provided.	X			
	Automated machinery components which have to be changed frequently must be capable of being removed and replaced easily and safely.	X			
	Access to the components must enable these tasks to be carried out with the necessary technical means in accordance with a specified operating method.	X			See manual
1.6.2	Access to operating position and serving points				
	Machinery must be designed and constructed in such a way as to allow access in safety to all areas where intervention is necessary during operation, adjustment and maintenance of the machinery.	X			EN ISO 12100

1.6.3	Isolation of energy sources				
	Machinery must be fitted with means to isolate it from all energy sources. Such isolators must be clearly identified.	X			EN 60204-1
	They must be capable of being locked if reconnection could endanger persons. Isolators must also be capable of being locked where an operator is unable, from any of the points to which he has access, to check that the energy is still cut off.	X			Complied
	In the case of machinery capable of being plugged into an electricity supply, removal of the plug is sufficient, provided that the operator can check from any of the points to which he has access that the plug remains removed.			X	No power plug
	After the energy is cut off, it must be possible to dissipate normally any energy remaining or stored in the circuits of the machinery without risk to persons.	X			Complied
	As an exception to the requirement laid down in the previous paragraphs, certain circuits may remain connected to their energy sources in order, for example, to hold parts, to protect information, to light interiors, etc. In this case, special steps must be taken to ensure operator safety.	X			IP2X and warning provided
1.6.4	Operator intervention				
	Machinery must be so designed, constructed and equipped that the need for operator intervention is limited.	X			EN ISO 12100
	If operator intervention cannot be avoided, it must be possible to carry it out easily and safely.	X			See above
1.6.5	Cleaning of internal parts				
	The machinery must be designed and constructed in such a way that it is possible to clean internal parts which have contained dangerous substances or preparations without entering them; any necessary unblocking must also be possible from the outside.	X			EN ISO 12100
	If it is impossible to avoid entering the machinery, it must be designed and constructed in such a way as to allow cleaning to take place safely.			X	
1.7	Indicators				
1.7.1	Information and warnings on the machinery				
	Information and warnings on the machinery should preferably be provided in the form of readily understandable symbols or pictograms.	X			
	Any written or verbal information and warnings must be expressed in an official Community language or languages, which may be determined in accordance with the Treaty by the Member State in which the machinery is placed on the market and/or put into service and may be accompanied, on request, by versions in any other official Community language or languages understood by the operators.	X			English

1.7.1.1	Information and information devices				
	The information needed to control machinery must be provided in a form that is unambiguous and easily understood. It must not be excessive to the extent of overloading the operator.	X			EN ISO 12100
	Visual display units or any other interactive means of communication between the operator and the machine must be easily understood and easy to use.	X			See above
1.7.1.2	Warning devices				
	Where the health and safety of persons may be endangered by a fault in the operation of unsupervised machinery, the machinery must be equipped in such a way as to give an appropriate acoustic or light signal as a warning.	X			
	Where machinery is equipped with warning devices these must be unambiguous and easily perceived. The operator must have facilities to check the operation of such warning devices at all times.	X			
	The requirements of the specific Community Directives concerning colours and safety signals must be complied with.	X			
1.7.2	Warning of residual risks				
	Where risks remain despite the inherent safe design measures, safeguarding and complementary protective measures adopted, the necessary warnings, including warning devices, must be provided.	X			
1.7.3	Marking of machinery				
	All machinery must be marked visibly, legibly and indelibly with the following minimum particulars:				
	— the business name and full address of the manufacturer and, where applicable, his authorised representative,	X			
	— designation of the machinery,	X			
	— the CE Marking (see Annex III),	X			
	— designation of series or type,	X			
	— serial number, if any,	X			
	— the year of construction, that is the year in which the manufacturing process is completed.	X			
	It is prohibited to pre-date or post-date the machinery when affixing the CE marking.	X			
	Furthermore, machinery designed and constructed for use in a potentially explosive atmosphere must be marked accordingly.			X	
	Machinery must also bear full information relevant to its type and essential for safe use. Such information is subject to the requirements set out in section 1.7.1.	X			
	Where a machine part must be handled during use with lifting equipment, its mass must be indicated legibly, indelibly and unambiguously.	X			

1.7.4	Instructions				
	All machinery must be accompanied by instructions in the official Community language or languages of the Member State in which it is placed on the market and/or put into service.	X			EN ISO 12100
	The instructions accompanying the machinery must be either 'Original instructions' or a 'Translation of the original instructions', in which case the translation must be accompanied by the original instructions.	X			EN ISO 12100
	By way of exception, the maintenance instructions intended for use by specialised personnel mandated by the manufacturer or his authorised representative may be supplied in only one Community language which the specialised personnel understand.	X			EN ISO 12100
	The instructions must be drafted in accordance with the principles set out below.	X			See below
1.7.4.1	General principles for the drafting of instructions				
	(a) The instructions must be drafted in one or more official Community languages. The words 'Original instructions' must appear on the language version(s) verified by the manufacturer or his authorised representative.	X			EN ISO 12100
	(b) Where no 'Original instructions' exist in the official language(s) of the country where the machinery is to be used, a translation into that/those language(s) must be provided by the manufacturer or his authorised representative or by the person bringing the machinery into the language area in question. The translations must bear the words 'Translation of the original instructions'.	X			EN ISO 12100
	(c) The contents of the instructions must cover not only the intended use of the machinery but also take into account any reasonably foreseeable misuse thereof.	X			EN ISO 12100
	(d) In the case of machinery intended for use by non-professional operators, the wording and layout of the instructions for use must take into account the level of general education and acumen that can reasonably be expected from such operators.	X			EN ISO 12100
1.7.4.2	Contents of the instructions				
	Each instruction manual must contain, where applicable, at least the following information:				
	(a) the business name and full address of the manufacturer and of his authorised representative;	X			
	(b) the designation of the machinery as marked on the machinery itself, except for the serial number (see section 1.7.3);	X			
	(c) the EC declaration of conformity, or a document setting out the contents of the EC declaration of conformity, showing the particulars of the machinery, not necessarily including the serial number and the signature;	X			
	(d) a general description of the machinery;	X			
	(e) the drawings, diagrams, descriptions and explanations necessary for the use, maintenance and repair of the machinery and for checking its correct functioning;	X			See above

	(f) a description of the workstation(s) likely to be occupied by operators;	X			See above
	(g) a description of the intended use of the machinery;	X			See above
	(h) warnings concerning ways in which the machinery must not be used that experience has shown might occur;	X			
	(i) assembly, installation and connection instructions, including drawings, diagrams and the means of attachment and the designation of the chassis or installation on which the machinery is to be mounted;	X			
	(j) instructions relating to installation and assembly for reducing noise or vibration;	X			
	(k) instructions for the putting into service and use of the machinery and, if necessary, instructions for the training of operators;	X			
	(l) information about the residual <u>risks</u> that remain despite the inherent safe design measures, safeguarding and complementary protective measures adopted;	X			See above
	(m) instructions on the protective measures to be taken by the user, including, where appropriate, the personal protective equipment to be provided;	X			See above
	(n) the essential characteristics of tools which may be fitted to the machinery;	X			See above
	(o) the conditions in which the machinery meets the requirement of stability during use, transportation, assembly, dismantling when out of service, testing or foreseeable breakdowns;	X			See above
	(p) instructions with a view to ensuring that transport, handling and storage operations can be made safely, giving the mass of the machinery and of its various parts where these are regularly to be transported separately;	X			See above
	(q) the operating method to be followed in the event of accident or breakdown; if a blockage is likely to occur, the operating method to be followed so as to enable the equipment to be safely unblocked;	X			See above
	(r) the description of the adjustment and maintenance operations that should be carried out by the user and the preventive maintenance measures that should be observed;	X			See above
	(s) instructions designed to enable adjustment and maintenance to be carried out safely, including the protective measures that should be taken during these operations;	X			See above
	(t) the specifications of the spare parts to be used, when these affect the health and safety of operators;	X			See above
	(u) the following information on airborne noise emissions:				
	— the A-weighted emission sound pressure level at workstations, where this exceeds 70 dB(A); where this level does not exceed 70 dB(A), this fact must be indicated,	X			< 80 dB(A) (see 1.1.1 e)
	— the peak C-weighted instantaneous sound pressure value at workstations, where this exceeds 63 Pa (130 dB in relation to 20 µPa),			X	See above

	— the A-weighted sound power level emitted by the machinery, where the A-weighted emission sound pressure level at workstations exceeds 80 dB(A).			X	
	These values must be either those actually measured for the machinery in question or those established on the basis of measurements taken for technically comparable machinery which is representative of the machinery to be produced.	X			
	In the case of very large machinery, instead of the A-weighted sound power level, the A-weighted emission sound pressure levels at specified positions around the machinery may be indicated.	X			< 80 dB(A)
	Where the harmonised standards are not applied, sound levels must be measured using the most appropriate method for the machinery. Whenever sound emission values are indicated the uncertainties surrounding these values must be specified. The operating conditions of the machinery during measurement and the measuring methods used must be described.	X			
	Where the workstation(s) are undefined or cannot be defined, A-weighted sound pressure levels must be measured at a distance of 1 metre from the surface of the machinery and at a height of 1,6 metres from the floor or access platform. The position and value of the maximum sound pressure must be indicated.	X			See above
	Where specific Community Directives lay down other requirements for the measurement of sound pressure levels or sound power levels, those Directives must be applied and the corresponding provisions of this section shall not apply;			X	2000/14/EC Noise directive for movable outdoor equipment
	(v) where machinery is likely to emit non-ionising radiation which may cause harm to persons, in particular persons with active or non-active implantable medical devices, information concerning the radiation emitted for the operator and exposed persons.			X	None
1.7.4.3.	Sales literature				
	Sales literature describing the machinery must not contradict the instructions as regards health and safety aspects. Sales literature describing the performance characteristics of machinery must contain the same information on emissions as is contained in the instructions.	X			

2	Supplementary essential health and safety requirements for certain categories of machinery			X	
2.1	Foodstuffs machinery and machinery for cosmetics or pharmaceutical products			X	
2.2	Portable hand-held and/or hand-guided machinery			X	
2.3	Machinery for working wood and material with similar physical characteristics			X	
3	Supplementary essential health and safety requirements to offset hazards due to the mobility of machinery			X	
4	Supplementary essential health and safety requirements to offset hazards due to lifting operations			X	
5	Supplementary essential health and safety requirements for machinery intended for underground work			X	
6	Supplementary essential health and safety requirements for machinery presenting particular hazards due to the lifting of persons			X	

EoF